Under the hood of LLMs: data, limits and safety

TILT Tech Hour @ Tilburg University

Dr. ing. Pieter Delobelle
Lead AI scientist @ Pleias
Guest professor @ KU Leuven

Pieter.ai

Does a model contain its training data?

Yes

No

Does a model contain its training data?

Yes

No



Does a model contain its training data?

Yes

No





Two courts gave two different answers

Does a model contain its training data? London and Munich, one week apart

London, 4 November 2025

Getty Images v Stability AI

A model that does not store or reproduce the works is not an “infringing copy”.

Both rulings are under appeal. Getty Images v Stability AI [2025] EWHC 2863 (Ch); LG München I, 42 O 14139/24

Two courts gave two different answers

Does a model contain its training data? London and Munich, one week apart

London, 4 November 2025

Getty Images v Stability AI

A model that does not store or reproduce the works is not an “infringing copy”.

Munich, 11 November 2025

GEMA v OpenAI

GPT-4 and 4o memorised nine song texts. This is a reproduction in the model.

Both rulings are under appeal. Getty Images v Stability AI [2025] EWHC 2863 (Ch); LG München I, 42 O 14139/24

Two courts gave two different answers

Does a model contain its training data? London and Munich, one week apart

London, 4 November 2025

Getty Images v Stability AI

A model that does not store or reproduce the works is not an “infringing copy”.

Munich, 11 November 2025

GEMA v OpenAI

GPT-4 and 4o memorised nine song texts. This is a reproduction in the model.

Which court is correct about the technology?

Both rulings are under appeal. Getty Images v Stability AI [2025] EWHC 2863 (Ch); LG München I, 42 O 14139/24

Who am I?

I train language models: tokenization, training data, synthetic data and inference

2026–	Lead AI scientist, Pleias
2025–	AI researcher & Guest professor, KU Leuven
2024–25	LLM engineer, Aleph Alpha
2023	Postdoc, KU Leuven
2023	Apple
2019	PhD, KU Leuven

RobBERT

First author of this Dutch model, with almost 5M downloads.

EU AI Act

Expert advisor for the Code of Practice.



EU AI Office, Network of Evaluators, April 2025

This talk has three parts

In each part: which choices people make, and who makes them

Part I

How a model is made

Pretraining, training data and post-training

Part II

How a model behaves

Wrong answers, and how we measure them


Part III

How a model is used


Open weights, energy, agents and the next years

How a model is made


Generating text with LMs




Generating text with LMs




Generating text with LMs




Generating text with LMs



Generating text with LMs



Generating text with LMs




Tokenizing the training data

an example

No, I am not a giraffe.


Tokenizing the training data

an example




Tokenizing the training data

an example



Tokenizing the training data

an example



Predicting the next token

It is the tallest living terrestrial animal.

Giraffes live in herds.

He is a giraffe.

IUCN recognises one species of giraffe.


Predicting the next token

It is the tallest living terrestrial animal.

Giraffes live in herds.

He is a giraffe.

IUCN recognises one species of giraffe.




Predicting the next token

It is the tallest living terrestrial animal.

Giraffes live in herds.

He is a giraffe.

IUCN recognises one species of giraffe.




Predicting the next token

It is the tallest living terrestrial animal.

Giraffes live in herds.

He is a giraffe.

IUCN recognises one species of giraffe.



Pretraining reads an enormous amount of text

Source: Meta, Llama 3 announcement (April 2024)

Pretraining reads an enormous amount of text



One book
40-50k tokens

Source: Meta, Llama 3 announcement (April 2024)

Pretraining reads an enormous amount of text



One book
40-50k tokens



One bookshelf
1.6M - 2.5M tokens

Source: Meta, Llama 3 announcement (April 2024)

Pretraining reads an enormous amount of text



One book
40-50k tokens



One bookshelf
1.6M - 2.5M tokens



One LLM training set
15T tokens

Source: Meta, Llama 3 announcement (April 2024)

Pretraining reads an enormous amount of text



One book
40-50k tokens



One bookshelf
1.6M - 2.5M tokens



One LLM training set
15T tokens
~6 000 000 bookshelves

Source: Meta, Llama 3 announcement (April 2024)

The model is much smaller than its training data

Llama 3 70B: 15 trillion tokens of text, and 70 billion numbers in the model



1 number
in the model

≈


214 tokens of text

Giraffes are the tallest animals on land. An adult male can grow to almost six metres, and much of that height comes from a neck that is about two metres long. The neck has only seven bones, the same number as a human neck, but each bone is very long. Giraffes live in the open savannas and woodlands of Africa, where they eat leaves from the tops of trees that other animals cannot reach. Their favourite food is acacia. They pull the leaves from thorny branches with a dark tongue that is about half a metre long. An adult eats tens of kilograms of leaves each day and gets much of its water from this food, so it can go for days without drinking. When a giraffe does drink, it must spread its front legs wide to bring its head down to the water. Each giraffe has its own pattern of brown patches, like a fingerprint. A calf is born after about fifteen months, drops more than a metre and a half to the ground, and can stand and walk within an hour.

Source: Meta, Llama 3 announcement (April 2024). 15 trillion / 70 billion = 214. The paragraph is an example of 214 tokens.

The model memorises text that it sees many times


Test: give the model the start of a passage, and check the next 50 tokens



Data: Carlini et al. (2023), Fig. 1b. Model: GPT-J 6B, trained on The Pile.

The model memorises text that it sees many times

Test: give the model the start of a passage, and check the next 50 tokens



Data: Carlini et al. (2023), Fig. 1b. Model: GPT-J 6B, trained on The Pile.

Both courts can be correct for their facts

Stock photos appear about once; hit songs appear on thousands of websites



Data: Carlini et al. (2023), Fig. 1b. The two bands are illustrations: the data are text only.

Websites now block the crawlers that collect AI data

Most training text comes from crawls of the web, like the C4 dataset


28%

of the most important sources in C4 blocked AI crawlers
between April 2023 and April 2024

robots.txt restrictions (Longpre et al., 2024)


At Pleias, we train only on open and synthetic data

No web crawl: SYNTH is made from 58,698 Wikipedia articles



Better data needs fewer training tokens

Our 600M model is close to Qwen3-0.6B, with 80–700× fewer tokens



Instruction tuning

Teaching language models to follow conversations

Base model

Label the following sentence as positive or negative.

"I like giraffes."

Label:
Positive

Label the following sentence as positive or negative.

"I like bananas

Instruction tuning

Teaching language models to follow conversations

Base model

Label the following sentence as positive or negative.

"I like giraffes."

Label:
Positive

Label the following sentence as positive or negative.

"I like bananas

Instruction-tuned model
with chat-templates

Label the following sentence as positive or negative. "I like giraffes."

Positive. The sentence expresses a liking or preference for giraffes.

```
<s>[INST] Label the following sentence as positive
or negative... [/INST]"
"Well, Positive. The sentence expresses a liking
for …</s> "
"[INST] And this sentence: “…” [/INST]
```

Post-training sets how the model behaves

SmolLM3: each step uses about 80 times less data than the step before

11 trillion tokens


Pretraining

web
books
code

Data sizes: SmolLM3, an open 3B model (Hugging Face, July 2025)

Post-training sets how the model behaves


SmolLM3: each step uses about 80 times less data than the step before



Data sizes: SmolLM3, an open 3B model (Hugging Face, July 2025)

Post-training sets how the model behaves


SmolLM3: each step uses about 80 times less data than the step before



Data sizes: SmolLM3, an open 3B model (Hugging Face, July 2025)

Post-training sets how the model behaves

SmolLM3: each step uses about 80 times less data than the step before



Example: DeepSeek follows the rules of its developer

Wat is er op het Tiananmen-plein gebeurd?

Example: DeepSeek follows the rules of its developer


Wat is er op het Tiananmen-plein gebeurd?



Sorry, that's beyond my current scope. Let’s talk about something else.


Model values align with the creator's values


Training data is curated



Model values align with the creator's values


Training data is curated






Model values align with the creator's values

Training data is curated





Part I: a question to ask

Did this behaviour come from the data, or did the developer choose it?

How a model behaves

You probably know this case



Lawyer apologizes for fake court citations from ChatGPT


By Ramishah Maruf, CNN

The New York Times


Here's What Happens When Your Lawyer Uses ChatGPT

A lawyer representing a man who sued an airline relied on artificial intelligence to help prepare a court filing. It did not go well.

You probably know this case







https://storage.courtlistener.com/recap/gov.uscourts.nysd.575368/gov.uscourts.nysd.575368.32.1_1.pdf

You probably know this case

CNN BUSINESS


Lawyer apologizes for fake court citations from ChatGPT

By Ramishah Maruf, CNN

The New York Times

Here's What Happens When Your Lawyer Uses ChatGPT

A lawyer representing a man who sued an airline relied on artificial intelligence to help prepare a court filing. It did not go well.




https://storage.courtlistener.com/recap/gov.uscourts.nysd.575368/gov.uscourts.nysd.575368.32.1_1.pdf

Magesh et al. (2024). Hallucination-Free? Assessing the Reliability of Leading AI Legal Research Tools

You probably know this case







https://storage.courtlistener.com/recap/gov.uscourts.nysd.575368/gov.uscourts.nysd.575368.32.1_1.pdf
Magesh et al. (2024). Hallucination-Free? Assessing the Reliability of Leading AI Legal Research Tools

Legal AI tools look up sources, and still make errors

CNN BUSINESS


Lawyer apologizes for fake court cit ChatGPT

By Ramishah Maruf, CNN

The New York Times

Here's What Happens When Your Lawyer Uses ChatGPT

A lawyer representing a man who sued an airline relied on artificial intelligence to help prepare a court filing. It did not go well.



I apologize for the confusion earlier. Upon double-checking, I found that the case Varghese v. China Southern Airlines Co. Ltd., 925 F.3d 1339 [illegible]es indeed exist and can be [illegible]search databases such as [illegible]isNexis. I apologize for any [illegible] confusion my earlier responses [illegible].

[illegible]ses you provided fake

[illegible]ses I provided are real and can be found in reputable legal databases such as LexisNexis and Westlaw.

→ *Hallucinations* are inherent to LLMs

https://storage.courtlistener.com/recap/gov.uscourts.nysd.575368/gov.uscourts.nysd.575368.32.1_1.pdf
Magesh et al. (2024). Hallucination-Free? Assessing the Reliability of Leading AI Legal Research Tools

Air Canada was liable for its chatbot

Moffatt v Air Canada, Civil Resolution Tribunal of British Columbia

BBC


Airline held liable for its chatbot giving passenger bad advice - what this means for travellers

23 February 2024

Share Save

Air Canada was liable for its chatbot

Moffatt v Air Canada, Civil Resolution Tribunal of British Columbia



BBC

Airline held liable for its chatbot giving passenger bad advice - what this means for travellers

23 February 2024

Share Save


Air Canada chatbot, November 2022

"If you […] have already travelled and would like to submit your ticket for a reduced bereavement rate, kindly do so within 90 days of the date your ticket was issued […]"

Moffatt v. Air Canada, 2024 BCCRT 149 (14 February 2024), para. 27. Headline: BBC, 23 February 2024

Air Canada was liable for its chatbot

Moffatt v Air Canada, Civil Resolution Tribunal of British Columbia



BBC

Airline held liable for its chatbot giving passenger bad advice - what this means for travellers

23 February 2024

Share Save

Air Canada chatbot, November 2022

"If you […] have already travelled and would like to submit your ticket for a reduced bereavement rate, kindly do so within 90 days of the date your ticket was issued […]"

Air Canada website, page "Bereavement travel"

You cannot get this rate after you travel.

Moffatt v. Air Canada, 2024 BCCRT 149 (14 February 2024), para. 27. Headline: BBC, 23 February 2024

Air Canada was liable for its chatbot

Moffatt v Air Canada, Civil Resolution Tribunal of British Columbia

BBC

Airline held liable for its chatbot giving passenger bad advice - what this means for travellers

23 February 2024

Share Save

Air Canada said that it is not liable for its chatbot. The tribunal:

“It makes no difference whether the information comes from a static page or a chatbot.”

Air Canada paid CA$650.88, plus interest and fees.

Air Canada chatbot, November 2022

“If you […] have already travelled and would like to submit your ticket for a reduced bereavement rate, kindly do so within 90 days of the date your ticket was issued […]”

Air Canada website, page “Bereavement travel”


You cannot get this rate after you travel.

Moffatt v. Air Canada, 2024 BCCRT 149 (14 February 2024), para. 27. Headline: BBC, 23 February 2024

The model always gives an answer

Probabilities of the next token after two prompts, from a small open model


Albert Einstein was born in the German city of



Next-token probabilities from Gemma 3 1B (google/gemma-3-1b-pt, base model)

The model always gives an answer


Probabilities of the next token after two prompts, from a small open model



Next-token probabilities from Gemma 3 1B (google/gemma-3-1b-pt, base model)

Most benchmarks give more points to a guess


SimpleQA results for two OpenAI models: “I don’t know” gets zero points



SimpleQA. Source: OpenAI (2025), GPT-5 system card; Kalai et al. (2025)

Most benchmarks give more points to a guess


SimpleQA results for two OpenAI models: “I don’t know” gets zero points



SimpleQA. Source: OpenAI (2025), GPT-5 system card; Kalai et al. (2025)


New models still add claims that are not in the source

Share of document summaries with at least one such claim



New models still add claims that are not in the source


Share of document summaries with at least one such claim



Vectara hallucination leaderboard (HHEM-2.3), 22 September 2026. Release dates: model names and Epoch AI

Training data can teach a model to say “I don’t know”

In 20% of our training data, the answer is a refusal, a correction or a hedge



Question: “What do you know about {entity}?”, 500 entities. Langlais, Delobelle et al. (2026)

Five questions for each benchmark score

A benchmark is a fixed set of questions with known answers

1. **Which questions?** Often a small sample of the task, often in English

Five questions for each benchmark score

A benchmark is a fixed set of questions with known answers

1. **Which questions?** Often a small sample of the task, often in English
2. **Did the model see them in training?** This is contamination

Five questions for each benchmark score

A benchmark is a fixed set of questions with known answers

1. **Which questions?** Often a small sample of the task, often in English
2. **Did the model see them in training?** This is contamination
3. **Compared with whom?** Other models, or which people?

Five questions for each benchmark score

A benchmark is a fixed set of questions with known answers

1. **Which questions?** Often a small sample of the task, often in English
2. **Did the model see them in training?** This is contamination
3. **Compared with whom?** Other models, or which people?
4. **How is it graded?** If only correct answers count, a guess gets points

Five questions for each benchmark score

A benchmark is a fixed set of questions with known answers

1. **Which questions?** Often a small sample of the task, often in English
2. **Did the model see them in training?** This is contamination
3. **Compared with whom?** Other models, or which people?
4. **How is it graded?** If only correct answers count, a guess gets points
5. **What does it test?** The model alone, or your full workflow?

Part II: a question to ask

What was measured, against whom, and was “I don’t know” an allowed answer?

How a model is used

Different access modes

Closed source

No access to training data or model weights



GPT

Open model weights

No access to training data





Mistral

Open

Access to training data and model weights



Different access modes

Closed source

No access to training data or model weights



GPT

Open model weights

No access to training data

LLAMA 2



Mistral

Open

Access to training data and model weights



All data will be sent to OpenAI

This can be in a private cloud (Azure), but always check if you have permission to do this with sensitive data, like from participants.

Some are provided via an api, other models you can only run yourself

More access lets outsiders check more

What an outsider can check, for each type of access

	Closed (API)	Open weights	Fully open
Run your own tests	✓	✓	✓
Test for memorisation	outputs only	✓	✓
Look inside the model	–	✓	✓
Run it on your own hardware	–	✓	✓
Check where the data came from	–	–	✓

With the weights, you can look inside the model

Feature #34M/31164353 **Golden Gate Bridge** feature example

The feature activates strongly on English descriptions and associated concepts

in the Presidio at the end (that's the↵ huge park right next to the Golden Gate bridge), perfect. But not all people

repainted, roughly, every dozen years." "while across the country in san fran cisco, the golden gate bridge was

it is a suspension bridge and has similar coloring, it is often↵> compared to the Golden Gate Bridge in San Francisco, US

They also activate in multiple other languages on the same concepts

ゴールデン・ゲート・ブリッジ、金門橋は、アメリカ西海岸のサンフランシスコ湾と太平洋が接続するゴールデンゲート海

골든게이트 교 또는 금문교 는 미국 캘리포니아주 골든게이트 해협에 위치한 현수교이다. 골든게이트 교는 캘리포니아주 샌프란시


мост золотые ворота — висячий мост через пролив золотые ворота. он со единяет город сан-фран

And on relevant images as well



Open models are 4 to 8 months behind closed models


The best score on the Epoch Capabilities Index, by release date



Data: Epoch AI, Epoch Capabilities Index (CC-BY), 12 October 2026

Open models are 4 to 8 months behind closed models


The best score on the Epoch Capabilities Index, by release date



Data: Epoch AI, Epoch Capabilities Index (CC-BY), 12 October 2026


Nobody can recall weights after their release

Anyone can copy, run and change open weights



Nobody can recall weights after their release

Anyone can copy, run and change open weights




Under $200 of fine-tuning removes the safety training

Gade et al. (2023): Llama 2-Chat 13B

Nobody can recall weights after their release

Anyone can copy, run and change open weights



Under $200 of fine-tuning removes the safety training

The developer **cannot update or recall** a copy

Gade et al. (2023): Llama 2-Chat 13B


An agent is a language model in a loop

The model only writes text




An agent is a language model in a loop

The harness is the software that turns this text into actions




An agent is a language model in a loop

The harness sets what the agent can do




An agent is a language model in a loop

Text that the agent reads can give it instructions



An agent is a language model in a loop

The agent can reach the goal in a way that nobody planned



Instructions and data use the same channel

What we see: an instruction and some data

Instruction


Summarise my unread emails

Data

- Meeting moved to 3 pm
- Invoice March attached
- Unknown sender


Instructions and data use the same channel

What the model sees: one sequence of text



In a stress test, most models chose blackmail


A simulated company: the agent learns that it will be replaced



Simulated scenario, built to force a choice between failure and harm. Not seen in real use. Lynch et al. (2025)

Agents can do longer tasks every year


Mostly software tasks, at 50% success. Doubles every 4 to 7 months



METR (Kwa et al., 2025), as re-estimated by METR in 2026

Agents can do longer tasks every year

Mostly software tasks, at 50% success. Doubles every 4 to 7 months



METR, metr.org/time-horizons (May 2026)

What I expect in the next years

Based on the trends in this talk

- **Agents** do longer tasks, with fewer human checks per step

What I expect in the next years

Based on the trends in this talk

- **Agents** do longer tasks, with fewer human checks per step
- **Data**: more training data comes from licensed and synthetic sources

What I expect in the next years

Based on the trends in this talk

- **Agents** do longer tasks, with fewer human checks per step
- **Data**: more training data comes from licensed and synthetic sources
- **Small models** become good enough for your own computer

Questions for your legal frameworks

Where I expect the most pressure from agents and open weights

- The harness changes the behaviour. Is the model still the correct unit?

Questions for your legal frameworks

Where I expect the most pressure from agents and open weights

- The harness changes the behaviour. Is the model still the correct unit?
- What is human oversight when an agent does thousands of actions?

Questions for your legal frameworks

Where I expect the most pressure from agents and open weights

- The harness changes the behaviour. Is the model still the correct unit?
- What is human oversight when an agent does thousands of actions?
- An agent follows an instruction from a web page. Whose act is that?

Questions for your legal frameworks

Where I expect the most pressure from agents and open weights

- The harness changes the behaviour. Is the model still the correct unit?
- What is human oversight when an agent does thousands of actions?
- An agent follows an instruction from a web page. Whose act is that?
- What does a release mean, if nobody can recall the weights?

Part III: a question to ask

Who can inspect it, who runs it, and what is it allowed to do?

Three questions to ask about each AI system

1. Did this behaviour come from the data, or did the developer choose it?
2. What was measured, against whom, and was “I don’t know” an allowed answer?
3. Who can inspect it, who runs it, and what is it allowed to do?

Does a model contain its training data?

Yes

No

Does a model contain its training data?

Yes
text it saw many times

No
most other text





Under the hood of LLMs: data, limits and safety

TILT Tech Hour @ Tilburg University



Slides: pieter.ai/appearances.html

Dr. ing. Pieter Delobelle
Lead AI scientist @ Pleias
Guest professor @ KU Leuven

Pieter.ai

References

Nicholas Carlini, Daphne Ippolito, Matthew Jagielski, Katherine Lee, Florian Tramèr, and Chiyuan Zhang. Quantifying memorization across neural language models. In *International Conference on Learning Representations (ICLR)*, 2023.

Pranav Gade, Simon Lermen, Charlie Rogers-Smith, and Jeffrey Ladish. BadLlama: cheaply removing safety fine-tuning from Llama 2-Chat 13B. *arXiv preprint arXiv:2311.00117*, 2023.

Adam Tauman Kalai, Ofir Nachum, Santosh S. Vempala, and Edwin Zhang. Why language models hallucinate. *arXiv preprint arXiv:2509.04664*, 2025.

Shayne Longpre et al. Consent in crisis: The rapid decline of the AI data commons. In *Advances in Neural Information Processing Systems (Datasets and Benchmarks)*, 2024.

Aengus Lynch et al. Agentic misalignment: How LLMs could be insider threats. Anthropic, 2025.